



# SCALABLE ALL-IN-ONE GNSS SMART ANTENNA SOLUTION



The A222 GNSS Smart Antenna is an affordable, portable solution with professional-level accuracy for agricultural, marine, GIS, mapping, and other applications.

Focus on the job-at-hand with fast start-up and reacquisition times, scalable accuracy, and an easy-to-see LED status indicator for power, GNSS, and DGNSS. The durable enclosure houses both antenna and receiver. It can be powered through various sources, making the A222 smart antenna ideal for a variety of applications. Dual-Serial, CAN, and pulse output options make this DGNSS receiver compatible with almost any interface.

A222 is supported by Hemisphere's easy-to-use Atlas Portal ([www.atlasgns.com](http://www.atlasgns.com)), which empowers you to update firmware and enable functionality, including Atlas subscriptions for accuracies from meter to sub-decimeter levels.

## Key Features

- Atlas® L-band corrections
- Athena™ RTK engine
- Scalable accuracy within a single product for different use cases
- Durable enclosure is proven to withstand the most aggressive environments
- Compact, low-profile design with fixed or magnetic mounting options are ideal for portable and dynamic applications

## GNSS Receiver Specifications

**Receiver Type:** Scalable dual-frequency, multi-GNSS RTK

**Signals Received:** GPS L1CA/L1P/L1C/L2P/L2C  
GLONASS G1/G2/P1/P2  
BeiDou B1  
Galileo E1BC  
Atlas

**Channels:** 332

**GPS Sensitivity:** -142 dBm

**SBAS Tracking:** 3-channel, parallel tracking

**Update Rate:** 10 Hz standard, 20 Hz optional (with subscription)

**Timing (1 PPS)**

**Accuracy:** 20 ns

**Cold Start:** 60 s typical (no almanac, ephemeris, position, or RTC)

**Warm Start:** 30 s typical (almanac and RTC)

**Hot Start:** 10 s typical (almanac, ephemeris, position, and RTC)

**Maximum Speed:** 1,850 mph (999 kts)

**Maximum Altitude:** 18,288 m (60,000 ft)

## Accuracy

Positioning:	RMS (67%)	2DRMS (95%)
<b>Autonomous, no SA:</b> <sup>1</sup>	1.2 m	2.5 m
<b>SBAS:</b> <sup>1</sup>	0.3 m	0.6 m
<b>Atlas H10:</b> <sup>1,3</sup>	0.04 m	0.08 m
<b>Atlas H30:</b> <sup>1,3</sup>	0.15 m	0.3 m
<b>Atlas Basic:</b> <sup>1,3</sup>	0.50 m	1.0 m
<b>RTK:</b> <sup>1</sup>	8 mm + 1 ppm	15 mm + 2 ppm

## L-Band Receiver Specifications

**Receiver Type:** Single Channel

**Channels:** 1530 to 1560 MHz

**Sensitivity:** -130 dBm

**Channel Spacing:** 5 kHz

**Satellite Selection:** Manual or Automatic

**Reacquisition Time:** 15 sec (typical)

## Communications

**Ports:** 2 full-duplex RS-232, CAN<sup>4</sup>

**Baud Rates:** 4800 - 115200

**Correction I/O Protocol:** Hemisphere GNSS proprietary, RTCM v2.3 (DGPS), RTCM v3 (RTK)

**Data I/O Protocol:** NMEA 0183, NMEA 2000, Hemisphere GNSS binary

**Timing Output:** 1 PPS, CMOS, active low, falling edge sync, 10 k $\Omega$ , 10 pF load

## Event Marker

**Input:** CMOS, active low, falling edge sync, 10 k $\Omega$ , 10 pF load

## Power

**Input Voltage:** 7-32 VDC

**Power Consumption:** 4.1 W nominal (L1/L2 GPS/GLONASS; L-band)

**Current Consumption:** 0.35 A nominal (L1/L2 GPS/GLONASS; L-band)

**Power Isolation:** No

**Reverse Polarity Protection:** Yes

**Antenna Voltage:** Internal Antenna

## Environmental

**Operating Temperature:** -40°C to +70°C (-40°F to +158°F)

**Storage Temperature:** -40°C to +85°C (-40°F to +185°F)

**Humidity:** 95% non-condensing

**Mechanical Shock:** EP455 Section 5.41.1 Operational

**Vibration:** EP455 Section 5.15.1 Random

**EMC:** CE (ISO 14982 Emissions and Immunity), FCC Part 15, Subpart B, CISPR 22

**Enclosure:** IP67

## Mechanical

**Dimensions:** 15.8 L x 15.8 W x 7.9 H (cm)  
6.2 L x 6.2 W x 3.2 H (in)

**Weight:** < 1.05 kg (< 2.53 lbs)

**Status Indications (LED):** Power, GNSS Lock

**Power/Data Connector:** 12-pin male (metal)

**Antenna Mounting:** 1-14 UNS-2A female adapter, 5/8-11 UNC 2B adapter, flat mount available

1. Depends on multipath environment, number of satellites in view, satellite geometry, and ionospheric activity
2. Depends also on baseline length
3. Hemisphere GNSS Proprietary



## Hemisphere GNSS

8515 E. Anderson Drive  
Scottsdale, AZ 85255, USA

Phone: +1 (480) 348-6380  
Toll-Free: +1 (855) 203-1770  
Fax: +1 (480) 270-5070

precision@hgns.com  
www.hgns.com